



# ID Tubing Probes



- Part Number Example: **VMBFMF-.720MR-110T**, Flexible, Mag Bias, Ferritic Bobbin, .720" Diameter, Mid Range Frequency (50-500 kHz), 110 Foot Long Shaft, 3/8" Type T Nylon. Typically used for u-bend stainless steel tubing application.
- Part Number Example: **VMBBNF-.830VLF-83PE**, Barnacle scrapper, non magnetic, Ferritic Bobbin, .830" Diameter, Very Low Frequency (5-100 kHz), 83 Foot Long Shaft, 7/16" Polyethylene. Typically used for straight Admiralty Brass tubing application.
- Unique, Titanium Coil Cover for Greater Wear Resistance and Protection

VM	B	X	X	X	-	.XXX	XX	-	.XXX	X
										<b>T 5/16</b> 5/16 Type T Nylon <b>T</b> 3/8 Type T Nylon <b>H</b> 3/8 Type H Nylon <b>PE</b> 7/16 Polyethylene  Length of Shaft in Feet
										<b>H</b> 100 kHz – 1 MHz <b>MR</b> 50 – 500 kHz <b>LF</b> 20 – 200 kHz <b>VLF</b> 5 – 100 kHz <b>ULF</b> 1 - 20 kHz  Probe Diameter in Inches
										<b>F</b> Ferritic Bobbin – Higher Sensitivity <b>D</b> Delrin Bobbin  <b>N</b> No Magnet <b>M</b> Mag Bias <b>H</b> High Mag Bias  <b>B</b> Barnacle Scrapper <b>C</b> Chamfered Barnacle Scrapper <b>F</b> Flexible
Bobbin Probe										

